

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Issue date: 13/08/2025 Revision date: 13/08/2025 Supersedes: 05/04/2023 Version: 3.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form Article

Name Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

UN-No. (ADR) 3480

Product code BU Direct Fastening

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture For professional use only

Electrical batteries and accumulators

1.4. Supplier's details

Supplier Department issuing data specification sheet

Hilti (Hong Kong) Ltd. Hilti AG

701-704, 7/F, Tower A, Manulife Financial Centre Feldkircherstraße 100 223 Wai Yip Street, Kwun Tong FL 9494 Schaan

HK Kowloon Liechtenstein
Hong Kong T +423 234 2111

T +852 27734 700 product.compliance-direct.fastening@hilti.com

hksales@hilti.com

1.5. Emergency phone number

Emergency number Emergency CONTACT (24-Hour-Number):

GBK GmbH Global Regulatory Compliance

+49 (0)6132-84463

+852 27734 700

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Not classified

Adverse physicochemical, human health and

No additional information available

environmental effects

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

No labelling applicable

13/08/2025 HK - en 1/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification

For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand Temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately.

However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be breaked at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments

Lithium Ion rechercheable battery pack:

Name/Type Energy content (Wh)

16S3P ANR26650 396

This product contains a positive electrode (Lithium iron phosphate), a negative electrode

(graphite), electrolyte and binder.

The physical form of the product, however, precludes exposure to workers under normal $\,$

conditions of use.

This mixture does not contain any substances to be mentioned according to the applicable regulations

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general

First-aid measures after inhalation

If the electrolyte is leaking out of the battery pack, the following measures have to be taken. Allow affected person to breathe fresh air. Allow the victim to rest. If necessary seek

medical advice.

First-aid measures after skin contact

Remove affected clothing and wash all exposed skin area with mild soap and water.

First-aid measures after eye contact

followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

First-aid measures after ingestion Rin

persists.

Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects

Potential adverse human health effects and

symptoms

Not expected to present a significant hazard under anticipated conditions of normal use. This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Severely irritant to skin. Irritation: may cause irritation to the respiratory system.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

13/08/2025 HK - en 2/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media Cool batteries and accumulators with water jet. In case of fire in the surroundings: Use

extinguishing agent suitable for surrounding fire.

5.2. Specific hazards arising from the chemical

Fire hazard Water may not extinguish burning batteries but will cool adjacent batteries and control the

spread of fire. Burning batteries will burn themselves out. Virtually all fires involving lithium batteries can be controlled by flooding with water. However, the contents of the battery will react with water and form hydrogen gas. In a confined space, hydrogen gas can form an

explosive mixture. In this situation, smothering agents are recomended.

Hazardous decomposition products in case of fire Formation of toxic gases is possible during heating or in case of fire. Water might react with

released Lithium hexafluorophosphate to highly toxic gaseous hydrogen fluoride.

5.3. Special protective actions for fire-fighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures No flames, no sparks. Eliminate all sources of ignition. Isolate from fire, if possible, without

unnecessary risk. For further information refer to section 8: "Exposure controls/personal

protection". For further information refer to section 13.

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Equip cleanup crew with proper protection.

Emergency procedures Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Take up liquid spill into absorbent material.

Other information Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures

Precautions for safe handling Do not soak in water or seawater.

Do not expose to strong oxidizers.

Do not give a strong mechanical shock or fling.

Never disassemble, modify or deform.

Do not connect the positive terminal to the negative terminal with electrically conductive $% \left(1\right) =\left(1\right) \left(1$

material.

Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.

Do not throw into fire or expose to high temperatures (>85 $^{\circ}\text{C}$).

Do not connect the positive terminal to the negative terminal with electrically conductive

material. Charge within limits of 0°C to 45°C temperature. Discharge within limits of -20°C to +60°C temperature.

Always wash hands after handling the product.

13/08/2025 HK - en 3/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Additional hazards when processed Normal use of this product shall imply use in accordance with the instructions on the

packaging and in line with the expectations of a professional user.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Protect from heat and direct sunlight. Protect from moisture.

Storage area Store in a well-ventilated place.
Incompatible products Strong bases. Strong acids.
Incompatible materials Sources of ignition. Direct sunlight.

Information on mixed storage Store away from water.

Do not store together with electrically conductive materials.

The accu-pack should be stored at 30 to 50% of the charging capacity.

Avoid storing in places where it is exposed to static electricity.

Storage temperature -20 – 45 °C (humidity: 0% - 80%)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls Ensure adequate ventilation. If the electrolyte is leaking out of the battery pack, the following

measures have to be taken.

Other information Do not eat, drink or smoke when using this product.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection Wear protective gloves

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection Chemical goggles or safety glasses
Respiratory protection No additional information available

Personal protective equipment symbol(s)





8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state Solid
Colour Grey.
Odour Not available
Odour threshold Not available
Melting point Not available
Freezing point Not applicable

13/08/2025 HK - en 4/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Boiling point Not available Flammability Non flammable Lower explosion limit Not applicable Upper explosion limit Not applicable Flash point Not applicable Auto-ignition temperature Not applicable Not available Decomposition temperature Not available Not available pH solution Viscosity, kinematic (calculated value) (40 °C) Not applicable Partition coefficient n-octanol/water (Log Kow) Not available Vapour pressure Not available Vapour pressure at 50°C Not available Not available Density Not available Relative density Relative vapour density at 20°C Not applicable Not available Solubility Not available Particle size

9.2. Data relevant with regard to physical hazard classes (supplemental)

Explosive limits Not applicable

Explosive properties Risk of explosion by shock, friction, fire or other sources of ignition.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Heating may cause a fire or explosion.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Water, humidity.

10.5. Incompatible materials

Conductive materials, water, seawater, strong oxidizers and strong acids.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) Not classified (Based on available data, the classification criteria are not met) Acute toxicity (dermal) Not classified (Based on available data, the classification criteria are not met) Acute toxicity (inhalation) Not classified (Based on available data, the classification criteria are not met) Skin corrosion/irritation Not classified (Based on available data, the classification criteria are not met) Serious eye damage/irritation Not classified (Based on available data, the classification criteria are not met) Respiratory or skin sensitization Not classified (Based on available data, the classification criteria are not met) Germ cell mutagenicity Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Carcinogenicity Reproductive toxicity Not classified (Based on available data, the classification criteria are not met) STOT-single exposure Not classified (Based on available data, the classification criteria are not met)

13/08/2025 HK - en 5/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

STOT-repeated exposure

Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard

Not classified (Based on available data, the classification criteria are not met)

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Viscosity, kinematic

Potential adverse human health effects and symptoms

This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Severely irritant to skin. Irritation: may cause irritation to the respiratory system.

Other information

When used and handled according to specifications, the product does not have any harmful

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute)

Hazardous to the aquatic environment, long-term (chronic)

Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)

effects according to our experience and the information provided to us.

Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)

12.2. Persistence and degradability

Li-lon Battery 16S3P ANR26650 for FX 3-A tool

Persistence and degradability Not established.

12.3. Bioaccumulative potential

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Bioaccumulative potential No additional information available

12.4. Mobility in soil

Li-lon Battery 16S3P ANR26650 for FX 3-A tool

Mobility in soil No additional information available

12.5. Other adverse effects

Ozone Not classified (Based on available data, the classification criteria are not met)

Other adverse effects No additional information available

Other information Do not allow battery packs to penetrate the soil.

The battery cell may corrode and electrolyte may leak.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations Dispose in a safe manner in accordance with local/national regulations. Refer to

manufacturer/supplier for information on recovery/recycling.

Ecological waste information Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID number					
UN 3480	UN 3480	UN 3480	UN 3480	UN 3480	

13/08/2025 HK - en 6/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shippin	g name			
LITHIUM ION BATTERIES	LITHIUM ION BATTERIES	Lithium ion batteries	LITHIUM ION BATTERIES	LITHIUM ION BATTERIES
Transport document descr	iption			1
UN 3480 LITHIUM ION BATTERIES, 9, (E)	UN 3480 LITHIUM ION BATTERIES, 9	UN 3480 Lithium ion batteries, 9	UN 3480 LITHIUM ION BATTERIES, 9	UN 3480 LITHIUM ION BATTERIES, 9
14.3. Transport hazard o	class(es)		•	
9	9	9	9	9
	3			
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information	n available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) M4

Special provisions (ADR) 230, 310, 348, 376, 377, 387, 636

Limited quantities (ADR) 0
Excepted quantities (ADR) E0

Packing instructions (ADR) P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906

Transport category (ADR) 2
Tunnel restriction code (ADR) E

Transport by sea

Special provisions (IMDG) 188, 230, 310, 348, 376, 377, 384, 387

Limited quantities (IMDG) 0
Excepted quantities (IMDG) E

Packing instructions (IMDG) P903, P908, P909 , P910, P911, LP903, LP904, LP905, LP906

EmS-No. (Fire)F-AEmS-No. (Spillage)S-IStowage category (IMDG)AStowage and handling (IMDG)SW19

Flash point (IMDG)

Properties and observations (IMDG) Electrical batteries containing lithium ion may react (e.g. flame, heat, emission of toxic,

corrosive or flammable gases or vapours) or disassemble due to damage, defects or short

circuit.

Air transport

PCA Excepted quantities (IATA) E0
PCA Limited quantities (IATA) Forbidden
PCA limited quantity max net quantity (IATA) Forbidden
PCA packing instructions (IATA) Forbidden

13/08/2025 HK - en 7/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

PCA max net quantity (IATA) Forbidden
CAO packing instructions (IATA) See 965
CAO max net quantity (IATA) See 965

Special provisions (IATA) A88, A99, A154, A183, A201, A213, A331, A334, A802

ERG code (IATA) 12FZ

Inland waterway transport

Classification code (ADN) M4

Special provisions (ADN) 188, 230, 310, 348, 376, 377, 387, 636, 677

Limited quantities (ADN) 0

Excepted quantities (ADN) E0

Equipment required (ADN) PP

Number of blue cones/lights (ADN) 0

Rail transport

Classification code (RID) M4

Special provisions (RID) 188, 230, 310, 348, _376, 377, 387, 636, 677

Limited quantities (RID) 0
Excepted quantities (RID) E0

Packing instructions (RID) P903, 908, 909, P910, P911, LP903, LP904, LP905, LP906

Transport category (RID) 2
Colis express (express parcels) (RID) CE2
Hazard identification number (RID) 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Regulatory reference Not listed on the United States TSCA (Toxic Substances Control Act) inventory.

SECTION 16: Other information

 Issue date
 8/13/2025

 Revision date
 8/13/2025

 Supersedes
 4/5/2023

Section	Changed item	Comments
1	Trade name	Modified
14	Transport information	Modified

Abbreviations and acronyms CAS-No. - Chemical Abstract Service number

ADN - European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DNEL - Derived-No Effect Level EC50 - Median effective concentration

ED - Endocrine disruptor

EC-No. - European Community number

13/08/2025 HK - en 8/9



Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

EN - European Standard

IATA - International Air Transport Association

IMDG - International Maritime Dangerous Goods

IOELV - Indicative Occupational Exposure Limit Value

LC50 - Median lethal concentration

LD50 - Median lethal dose

NOEC - No-Observed Effect Concentration

OECD - Organisation for Economic Co-operation and Development

N.O.S. - Not Otherwise Specified

OEL - Occupational Exposure Limit

PBT - Persistent Bioaccumulative Toxic

PNEC - Predicted No-Effect Concentration

 $\label{eq:REACH-Registration} \textbf{REACH-Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation}$

(EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS - Safety Data Sheet

STP - Sewage treatment plant

TLM - Median Tolerance Limit

TRGS - Technical Rules for Hazardous Substances

VOC - Volatile Organic Compounds

WGK - Water Hazard Class

vPvB - Very Persistent and Very Bioaccumulative

NOAEL - No-Observed Adverse Effect Level

NOAEC - No-Observed Adverse Effect Concentration

LOAEL - Lowest Observed Adverse Effect Level

A safety data sheet is not required for this product. This Product Safety Information Sheet

has been created on a voluntary basis.

Other information SDS UN HILTI

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

13/08/2025 HK - en 9/9